



# EcoTube™

# Milky

# Lens

EcoTube™ Milky LED Tubes

More vision comfortable and higher brightness, why not EcoTubes™? Eco Light Solutions EcoTube™ T8 LED Tubes are the most qualified replacements for conventional fluorescent T8 on the current market. Milky Lens makes EcoTube™ s emit very eye-comfortable light without any light spots. Meanwhile they adopt a quite number of SMD LEDs as lighting source, which maintains competitive brightness.



## Features:

- Even color and non-glare beams;
- Higher Brightness (Max. 1800lm);
- Most qualified replacements for conventional fluorescent;
- Easier retrofit with integrated power supply;
- 50% Energy saving;
- Good light quality and good heat dissipation;
- Minimum maintenance costs;
- Green and eco-friendly lighting source without mercury.

## Ordering Information

Part Number	Description	Unit
ECO-T84NW-T150	G4 IPS, Natural White, 150LEDs (3528 SMD), 0.6m, 100~130VAC, Milky Lens	pcs
ECO-T84NW-T300	G4 IPS, Natural White, 300LEDs (3528 SMD), 1.2m, 100~130VAC, Milky Lens	pcs
ECO-T84NW-T360	G4 IPS, Natural White, 360LEDs (3528 SMD), 1.5m, 100~130VAC, Milky Lens	pcs
ECO-T84NW-T2150	G4 IPS, Natural White, 150LEDs (3528 SMD), 0.6m, 190~277VAC, Milky Lens	pcs
ECO-T84NW-T2300	G4 IPS, Natural White, 300LEDs (3528 SMD), 1.2m, 190~277VAC, Milky Lens	pcs
ECO-T84NW-T2360	G4 IPS, Natural White, 360LEDs (3528 SMD), 1.5m, 190~277VAC, Milky Lens	pcs

## Technical Specifications

### Physical Specifications

Length	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
Weight	240g	490g	610g
Housing	Aluminum		
Cover	Milky PC		
Tube Diameter	T8		
Base Type	G13		
Work Environment	Indoor use (applicable for dry environment)		

### Electrical Specifications

	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
LED Quantity	150LEDs	300LEDs	360LEDs
Power Consumption	10W±2W	20W±2W	25W±2W
Input Voltage	100~130VAC/190~277VAC		
Power Factor	>0.92		
Lighting Source	SMD LEDs		
Operation Temperature	-20~40°C (-4~104°F)		

### Optical Specifications

	600 mm (1.96 ft)	1200 mm (3.93 ft)	1500 mm (4.92 ft)
--	------------------	-------------------	-------------------

Lumens	680~720 lm	1350~1450 lm	1700~1800 lm
Color Range	White		
Color Temperature	6000~6500K		
CRI	>65		
Beam Angle	120°		

[www.EcoLightSolutions.com](http://www.EcoLightSolutions.com)

Eco Light Solutions

[www.Ecolightsolutions.com](http://www.Ecolightsolutions.com)

[swerner@ecolightsolutions.com](mailto:swerner@ecolightsolutions.com)

P: 714 502- 0280

F: 714 502-0628